


S2 Webbing Slings, 2-ply, with two-sided secutex Coating

Double protection – far more durable. A real workhorse: SpanSet S2 webbing slings with secutex® protection on both sides. This material has an extremely high structural stability and adapts flexibly to sharp edges e.g. with rolled steel or concrete parts. Thus the pressure is evenly distributed, the belt material is protected and the service life extended.

More applications with crane brackets: With crane brackets at both ends you gain a lot of flexibility: Simply put one end of the sling through the bracket at the other end and you can work in perfect choker hitch. Apart from that the crane brackets simplify the connection with lifting beams and crane hooks working in basket hitch as the brackets only have a small contact surface.

- Webbing sling according to DIN EN 1492-1
- secutex® coating on both sides
- Suitable for severe conditions of use
- Extremely wear resistant

Double protection for the webbing sling



secutex® coating on both sides



S2 Webbing Sling according to DIN EN 1492-1, both Sides S2 coated, with 2 reinforced Crane Loops



Webbing sling profile ca. in mm	Load capacity in basket hitch kg	Load capacity single direct kg	Type	Loop size in mm	Item no.	Length L in mm					
						2.0	3.0	4.0	5.0	6.0	8.0
40 x 18	2000	1000	PB 1000-S2	300	25103000...	...015120	...015121	...015122	...015123	...015124	...015125
70 x 18	4000	2000	PB 2000-S2	300	25103000...	...015126	...015127	...015128	...015129	...015130	...015131
100 x 18	6000	3000	PB 3000-S2	400	25103000...	...015132	...015133	...015134	...015135	...015136	...015137
130 x 18	8000	4000	PB 4000-S2	400	25103000...	...015138	...015139	...015140	...015141	...015142	...015143
160 x 18	10000	5000	PB 5000-S2	500	25103000...	...015144	...015145	...015146	...015147	...015148	...015149
190 x 18	12000	6000	PB 6000-S2	700	25103000...	...015150	...015151	...015152	...015153	...015154	...015155
250 x 18	16000	8000	PB 8000-S2	800	25103000...	-	...015156	...015157	...015158	...015159	...015160
310 x 18	20000	10000	PB 10000-S2	1000	25103000...	-	...015161	...015162	...015163	...015164	...015165