

Hydraulic Torque Type HTWP Wrench Pumps

Type	Motor voltage	Version automatic control	Displacement 1st stage	Displacement 2nd stage	Displacement 3rd stage	Dimensions L x W x H in mm	Weight in kg	Item no.
Version with air engine 7 Bar (air)								
HTWP2140P	Standard	-	6.1 l/min	0.51 l/min	-	468x205x445	28	35151500015001
TPA07A	Premium	-	7.0 l/min	1.0 l/min	0.8 l/min	456x286x476	30	35151500035003
Version with electric engine 230V-1Ph-50Hz								
HTWP2142AR	Standard	Semi-automatic	3.9 l/min	0.36 l/min	-	468x205x445	34	35151500015002
TPE25A	Premium	Fully automatic	6.5 l/min	1.5 l/min	0.75 l/min	456x286x476	39	35151500035004



TPE25A



HTWP2142AR

Split Block Type HTWM with Couplers

- 4-way split block, including quick connect couplers and hydraulic hoses
- Suitable for use of up to 4 hydraulic wrenches from one pump


Type	Item no.
HTWM 4	35162000015014



HTWM4

Hydraulic Hoses Type HTWH for Torque Wrenches

Type	Length in m	Item no.
HTWH 4	4	35161000015005
HTWH 5	5	35161000015006
HTWH 6	6	35161000015007
HTWH 8	8	35161000015008
HTWH 10	10	35161000015009



HTWH4

Drip-free Couplers for Torque Wrenches Type CF and CM

Type	Thread size in inches	Description	Item no.
CF 4F	1/4" NPT IG	Female half coupler	35163000015008
CM 4F	1/4" NPT IG	Male half coupler	35163000015010



CF4F



CM4F